



QD Bushes

The taper-bored "QD" item easily fits over the tapered bush and tightening of the cap screws produces a tight fit on the shaft. The bush is easily removed from the hub by using the pull-up bolts as jack screws. Sizes available include QH, JA, SH, SDS, SD, SK, SF, E, F, J, M, N. All bushes are available in pilot bore, and can be re bored to suit the shaft requirements.

All bushes "JA" through "N" are drilled for Reverse Mounting.

Part No.	Max Bore	O.D.	A	B	C	D	No. Bolts	P.C.D
JA	25	50.8	26.9	9.5	17.4	34.9	3	42.2
QH	32	63.5	31.7	7.9	25.4	41.2	2	50.8
SH	35	68.3	33.3	11.1	22.2	47.5	3	57.2
SDS	42	80.9	34.9	12.7	22.2	55.5	3	68.3
SD	42	80.9	46.1	12.7	33.3	55.5	3	68.3
SK	55	98.4	49.2	14.2	34.9	71.4	3	84.1
SF	60	117.4	52.3	14.2	38.1	79.4	3	98.3
E	75	152.4	66.6	19.4	47.6	97.3	3	127.0
F	90	168.2	92.5	20.6	71.4	112.6	3	142.9
J	100	184.2	114.3	25.4	88.9	130.8	3	158.8
M	120	228.6	171.5	31.8	139.7	165.1	4	200.0
N	130	254.0	206.4	38.1	168.3	177.8	4	215.9

All dimensions in mm unless otherwise stated

