



Taper Bushes

Taper bushes are designed to give the following:-

1. Easy assembly.
2. Rapid dismantling of the pulley and other transmission equipment.
3. No special tool requirement except hexagonal allen key.

A large range of bores are available off the shelf which ensures that an immediate assembly can be made, thus avoiding costly factory down-time.

The bushes are machined with standard keyways. This, in addition to clamping screws is sufficient to meet the required torque.

Part No.		Stock Bore Sizes	OD	L
1008	mm	12, 14, 15, 16, 18, 19, 20, 22, 24, 25	35.0	22.2
	inch	1/2", 5/8", 3/4", 7/8", 1"		
1108	mm	12, 14, 15, 16, 18, 19, 20, 22, 24, 25, 28	38.0	22.2
	inch	1/2", 5/8", 3/4", 7/8", 15/16", 1", 1 1/16", 1 1/8"		
1210	mm	12, 14, 15, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32	47.5	25.4
	inch	1/2", 5/8", 11/16", 3/4", 13/16", 7/8", 1", 1 1/16", 1 1/8", 1 3/16", 1 1/4"		
1215	mm	12, 14, 16, 18, 19, 20, 22, 24, 25, 28, 30, 32	47.5	38.1
	inch	1/2", 9/16", 5/8", 11/16", 3/4", 7/8", 1", 1 1/16", 1 1/8", 1 3/16", 1 1/4"		
1610	mm	12, 14, 16, 18, 19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42	57.0	25.4
	inch	1/2", 5/8", 3/4", 13/16", 7/8", 1", 1 1/8", 1 1/4", 1 5/16, 1 3/8", 1 1/2", 1 5/8"		
1615	mm	12, 14, 16, 18, 19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42	57.0	38.1
	inch	1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 5/16", 1", 1 1/8", 1 3/16", 1 1/4"		
	inch	1 5/16", 1 3/8", 1 1/2", 1 5/8"		
2012	mm	16, 19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42, 45, 48, 50	70.0	31.8
	inch	3/4", 7/8", 1", 1 1/8", 1 1/4", 1 3/8", 1 1/2", 1 5/8", 1 3/4", 1 7/8", 2"		
2017	mm	19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42, 45, 48, 50	70.0	44.4
	inch	3/4", 13/16", 7/8", 15/16", 1", 1 1/16", 1 1/8", 1 5/16", 1 3/8"		
2517	mm	19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42, 45, 48, 50, 55, 60	85.5	44.5
	inch	3/4", 7/8", 1", 1 1/8", 1 1/4", 1 3/8", 1 1/2", 1 5/8", 1 3/4", 1 7/8", 2", 2 1/8",		
	inch	2 1/4", 2 3/8", 2 1/2"		
2525	mm	19, 20, 22, 24, 25, 28, 30, 32, 35, 38, 40, 42, 45, 48, 50, 55, 60	85.6	63.5
	inch	3/4", 7/8", 1", 1 1/8", 1 3/16", 1 3/8", 1 5/8"		
3020	mm	24, 25, 28, 30, 32, 35, 38, 40, 42, 45, 48, 50, 55, 60, 65, 70, 75	108.0	50.8
	inch	1", 1 1/8", 1 1/4", 1 3/8", 1 1/2", 1 5/8", 1 3/4", 1 7/8", 2", 2 1/8", 2 1/4", 2 3/8",		
	inch	2 1/2", 2 5/8", 2 3/4", 2 7/8", 3"		
3030	mm	32, 35, 38, 40, 42, 45, 48, 50, 55, 60, 65, 70, 75	108.0	76.2
	inch	1 1/4", 1 3/8", 1 7/16", 1 1/2", 1 5/8", 1 3/4", 1 7/8", 2", 2 1/8", 2 1/4", 2 3/8",		
	inch	2 1/2", 2 5/8", 2 3/4", 2 7/8", 3"		
3525	mm	35, 38, 40, 42, 45, 48, 50, 55, 60, 65, 70, 75, 80, 85, 90	127.0	63.5
3535	mm	35, 38, 40, 42, 45, 48, 50, 55, 60, 65, 70, 75, 80, 85, 90	127.0	88.9
	inch	1 1/2", 1 5/8", 1 3/4", 1 7/8", 2", 2 1/8", 2 1/4", 2 3/8", 2 1/2", 2 5/8", 2 3/4",		
	inch	2 7/8", 3", 3 1/8, 3 1/4", 3 3/8", 3 1/2"		
4030	mm	40, 42, 45, 48, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	146.0	76.2
4040	mm	40, 42, 45, 48, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	146.0	101.6
	inch	1 3/8", 1 3/4, 1 7/8", 2", 2 1/8", 2 1/4", 2 1/2", 2 5/8", 2 3/4",		
	inch	3", 3 1/4", 3 1/2", 3 3/4", 4"		
4535	mm	60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110	162.0	88.9
4545	mm	60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110	162.0	114.3
	inch	3", 3 1/8", 3 1/4", 3 3/8", 3 1/2", 3 3/4", 4", 4 1/4", 4 1/2"		
5040	mm	70, 95, 100, 110, 115, 120, 125	177.5	101.6
5050	mm	70, 95, 100, 110, 115, 120, 125	177.5	127.0

The first 2 digits of the part number are the maximum bore size in inches.

The second 2 digits of the part number are the length through bore in inches.