

Nu-T-Link & Super T-Link Open End Vee Belting

Stock No.	Top Width	Suit Pulley
Z/10	10.0	SPZ
A/13	13.0	SPA
B/17	17.0	SPB
C/22	22.0	SPC
S/25	25.0	SPS
D/32	32.0	SPD
SPA	SPA	SPA
SPB	SPB	SPB

Nu-T-Link & Super-T-Link is well established throughout the world as the V-belt that successfully overcomes many of the problems previously associated with standard V-belts. By utilising a composite polyurethane and polyester material Nu-T-Link & Super-T-Link ensures an extended operational life over rubber based V-belts. Replacing V-belts can often be a complex and time consuming chore. In many cases the drive assembly often needs to be dismantled to gain open access to both pulleys. However with the unique and patented 'T' link construction, the belt can be joined without dismantling the machine.



RED-GO Hollow Round Belting

Stock No.	Belt Dia.
REDGO05	5.0
REDGO06	6.0
REDGO08	8.0
REDGO10	10.0
REDGO13	13.0

Red-Go Polyurethane belting is ideal for conveying, live rollers and many other drives. It can be made up to any length and is quickly cut to length and installed on the job requiring no special tools. Available in 5 different sizes 5mm, 6mm, 8mm, 10mm & 13mm

